

# PROVING UNITS



## SPEC

PD430

PD440

PD690 Mk2

PD700



## Specification PD430 & PD440 Proving Unit

### PD430



#### Output Voltage:

first output = 50V nominal  
second output = 440V nominal (see graph)  
50Hz nominal

#### Operating Temperature Range:

-10 to 40C at max. 70% RH

**Batteries:** 6 x LR6 (MN1500) 1.5V Alkaline batteries or equivalent (included)

**Dimensions:** 143 x 84 x 50mm

**Weight:** 400g approx with batteries

### PD440



#### Output Voltage:

output = 440V nominal (see graph)  
50Hz nominal

#### Operating Temperature Range:

-10 to 40C at max. 70% RH

**Batteries:** 6 x LR6 (MN1500) 1.5V Alkaline batteries or equivalent (included)

**Dimensions:** 143 x 84 x 50mm

**Weight:** 400g approx with batteries



## Specification PD690 & PD700 Proving Unit

### PD690



#### Output Voltage:

700V nominal (see graph)  
50Hz nominal

#### Operating Temperature Range:

-10 to 40C at max. 70% RH

**Batteries:** 6 x LR6 (MN1500) 1.5V Alkaline batteries or equivalent (included)

**Dimensions:** 143 x 84 x 50mm

**Weight:** 400g approx with batteries

### PD700



#### Output Voltage:

first output = 50V nominal  
second output = 700V (see graph)  
50Hz nominal

#### Operating Temperature Range:

-10 to 40C at max. 70% RH

**Batteries:** 6 x LR6 (MN1500) 1.5V Alkaline batteries or equivalent (included)

**Dimensions:** 143 x 84 x 50mm

**Weight:** 400g approx with batteries

## Output Voltage

