

# DLRO10HDX

## 10 Amp Digital Low Resistance



- **NEW** Onboard memory storage for test results up to 200 records (HDX only)
- Download to PowerDB
- **NEW** interchangeable test lead terminations
- High or low output power selection for condition diagnosis
- Operates from battery or AC mains supply
- Protected to 600 V without blowing a fuse, test lead live voltage warning light
- Heavy duty case: IP 65 lid closed, IP54 operational
- Simple rotary switch selection of five test modes, including auto start on connection

### DESCRIPTION

Augmenting Megger's DLRO10 and 10X range the DLRO10HDX combines ultimate simplicity of operation with a rugged IP65 case designed for stable ground and bench operation and provides memory storage.

These units are powered from either rechargeable battery or mains power making it suitable for continuous testing in production line/repetitive use environments.

Rotary switch controls are simple and easy to operate in all weather conditions and with gloved hands. A large, clear, backlit LCD display is easy to read from a distance. The DLRO10HDX provides significantly enhanced compliance and is capable of delivering 10 A into measurements up to 250 mΩ and 1 A into measurements up to 2.5 Ω. The duration of each test may be up to 60 seconds.

The DLRO10HDX is rated CAT III 300 V provided the optional terminal cover is fitted to the instrument. Details of which can be found in the ordering information panel of this data sheet.

The DLRO10HDX provides five test modes each of which is selected through a simple rotary control on the Mode selection rotary switch. All memory functions, delete, download to PowerDB and recalling test results are also accessible via the Range Selection rotary switch.

A simple control panel enables easy navigation for configuration settings.

### Transport case



New – A high quality transport case which has enough storage space to store your lead set, an extension lead and a number of terminations.

The new transport case keeps all the users test leads together with the instrument, especially

useful when instruments are stored in a vehicle, ensuring everything needed is kept together and ready to test.

See separate transport case data sheet (part number TC\_DS\_V01) for more details

### History of 'Ducter' testing

For over 100 years the 'Ducter test' has been used to describe a simple test for measuring very low contact resistances and "Ducter", which is still used as a trade mark, was the name originally given to the low resistance ohmmeter manufactured by Megger. The name Ducter was registered by Megger in June 1908 and 'Ducter' has since become the industry standard.

**ADDITIONAL FEATURES AND BENEFITS**

- Rugged case well suited to transportation with shoulder strap and lead set pouch
- Removable lid facilitates easy test lead connection
- Operational ingress protection is IP 54 (battery power only) ensuring protection from the elements
- 7Ah lead acid battery provides extended operation and can be charged whilst operating from line power
- Rotary mode switch with bidirectional (current reversal with averaging cancels thermal EMFs), unidirectional, automatic, continuous and inductive modes
- Large, clear LCD display with backlight and contrast adjustment
- Auto power off function conserves battery

**APPLICATIONS**

The DLRO10HDX measures low resistance values in applications ranging from railways and aircraft to resistance of components in industry.

Any metallic joint can be measured but users must be aware of measurement limitations depending on application. For example, if a cable manufacturer plans to make resistive measurements on a thin wire, a low test current should be selected to prevent heating the wire thereby changing its resistance.

Measurements on electric motors and generators will be inductive and require the user to understand the inductive mode and charging process before a correct result is achieved.

The DLRO10HDX is well suited to measuring thick conductors, bonds and quality of welding because of its 10 A range for resistance values up to 250 mΩ.

Electromagnetic noise induced into the leads can interfere with a reading. A noise symbol alerts the user and prevents a measurement when the instrument detects noise above its threshold.

When dissimilar metals are joined a thermocouple effect is created. Users should select a bidirectional mode to ensure cancellation of this effect. The instrument measures with current flowing in both directions and averages the result.

Normal mode is initiated by pressing the 'Test' button after connecting the test leads to the unit under test. Continuity of all four connections is checked. Current is applied in both forward and reverse direction following which measurement is displayed.

Automatic mode is started as soon as the probes make contact. Forward and reverse current measurements are made and the average value is displayed. This mode is ideal when working with handspikes. Each time the probes are removed and reconnected to the load a new test will be performed without the need to press the test button.

**TEST modes**

Automatic unidirectional mode applies current in one direction only to speed up the measurement process.

However thermal EMF resulting from dissimilar metal bonds can cause lower accuracy. Test starts automatically when probes are connected.

Continuous mode allows repeated measurements to be made on the same sample. Simply connect the test leads and press the test button. The measurement is updated every three seconds until the circuit is broken.

Inductive mode is selected when measuring resistance on, for example, motors and generators. When measuring inductive loads it is necessary to wait for the voltage to stabilise as the inductive element is charged. Test leads are firmly connected to the device under test and the 'Test' button pressed. The instrument will pass the selected current through the sample continuously in one direction only and take repetitive readings that will gradually decrease to the true value as the voltage stabilises. The operator decides when the result is stable and presses the 'Test' button to terminate the test.

## ELECTRICAL SPECIFICATIONS

### Resistance/Current Ranges

The green resistance ranges on the keypad indicate low output power (<0.25 W) outputs. Red ranges indicate higher 2.5 W (1 A) and 25 W (10 A) power outputs.

### Resolution and Accuracy

Test current accuracy  $\pm 10\%$

Voltmeter input impedance >200 k $\Omega$

| Test current | Resistance range        | Resolution (as displayed) | Basic accuracy* | Full scale voltage | Max. power output |
|--------------|-------------------------|---------------------------|-----------------|--------------------|-------------------|
| 0.1 mA       | 0 to 2500.0 $\Omega$    | 0.1 $\Omega$              | $\pm 0.2\%$     | 25 mV              | 25 $\mu$ W        |
| 0.1 mA       | 0 to 250.00 $\Omega$    | 0.01 $\Omega$             | $\pm 0.2\%$     | 25 mV              | 2.5 $\mu$ W       |
| 1 mA         | 0 to 25.000 $\Omega$    | 1 m $\Omega$              | $\pm 0.2\%$     | 25 mV              | 25 $\mu$ W        |
| 10 mA        | 0 to 2500.0 m $\Omega$  | 0.1 m $\Omega$            | $\pm 0.2\%$     | 25mV               | 250 $\mu$ W       |
| 100 mA       | 0 to 250.00 m $\Omega$  | 0.01 m $\Omega$           | $\pm 0.2\%$     | 25 mV              | 2.5 mW            |
| 1 A          | 0 to 25.000 m $\Omega$  | 1 $\mu\Omega$             | $\pm 0.2\%$     | 25 mV              | 25 mW             |
| 10 A         | 0 to 2500.0 $\mu\Omega$ | 0.1 $\mu\Omega$           | $\pm 0.2\%$     | 25 mV              | 0.25 W            |
| 1 A          | 0 to 2500.0 m $\Omega$  | 0.1 m $\Omega$            | $\pm 0.2\%$     | 2.5 V              | 2.5 W             |
| 10 A         | 0 to 250.00 m $\Omega$  | 0.01 m $\Omega$           | $\pm 0.2\%$     | 2.5 V              | 25 W              |

\* The accuracy stated assumes forward and reverse measurements.

Inductive mode or unidirectional mode will introduce an undefined error if an external EMF is present.

Basic accuracy at reference conditions.

## GENERAL SPECIFICATIONS

**Temperature coefficient** < 0.01% per  $^{\circ}\text{C}$ , from 5  $^{\circ}\text{C}$  to 40  $^{\circ}\text{C}$

**Maximum altitude** 2000 m (6562 ft) to full safety specifications

**Display size/type** Main 5 digit + 2 x 5 digit secondary displays

**Battery type** 6 V, 7Ah sealed lead acid

**Voltage input range** 100 - 240 V 50 / 60 Hz 90 VA

**Charge time** 8 hours

**Backlight** LED backlight

**Battery life** >1000 Auto (3 sec) tests

**Auto power down** 300s

**Mode selection** Rotary switch

**Range selection** Rotary switch

**Memory features selection** Rotary switch

**Weight** 6.7 kg

**Case dimensions** L315 mm x W285 mm x H181 mm

**Pouch for test leads** Yes (lid mounted)

**Test leads** included depending on chosen option:  
DH4C lead set  
KC1 Kelvin Clip lead set

**IP rating** IP65 case closed, IP54 battery operation

**Record storage** 200 test records

**Safety rating**  
In accordance with IEC61010-1, CATIII 300V when used with optional terminal cover (details in ordering information)

**Operating temperature and humidity**  
-10  $^{\circ}\text{C}$  to +50  $^{\circ}\text{C}$

(14  $^{\circ}\text{F}$  to 122  $^{\circ}\text{F}$ ) <90% RH

**Reference conditions** 20  $^{\circ}\text{C}$   $\pm 3$   $^{\circ}\text{C}$

**Storage temperature and humidity**  
-25  $^{\circ}\text{C}$  to +60  $^{\circ}\text{C}$ , <90% RH

### EMC

In accordance with IEC61326-1 (Heavy industrial)

### Noise rejection

Less than 1%  $\pm 20$  digits additional error with 100 mV peak 50/60 Hz. on the potential leads. Warning will show if hum or noise exceeds this level.

### Maximum lead resistance

100 m $\Omega$  total for 10 A operation irrespective of battery condition.

## OPTIONAL TERMINAL COVER



The CAT III 300 V rating on the DLRO10HDX is only valid when the instrument is fitted with the optional terminal cover to provide the required creepage and clearances at the instrument terminals. Although the terminal cover may be used

with any test leads, only the Megger DH4, DH5 and DP1-C duplex handspikes, and KC2-C insulated kelvin clips have suitable probe insulation to comply with the requirements of IEC61010-1 and the CATIII 300 V rating.



## SUPPLIED LEADSET OPTIONS



DLRO10HDX



+ DH4-C probe 1.5 m leads



+ KC1 Kelvin clip 3 m leads

+ No test leads supplied



Model name

Language

Plug/Mains lead

|           |   |  |   |     |  |   |   |  |
|-----------|---|--|---|-----|--|---|---|--|
| DLRO10HDX | - |  | - | L G |  | - | P |  |
|-----------|---|--|---|-----|--|---|---|--|

**SELECT A LEADSET**
**NLS** (No Leadset)

**DH4C** (DH4-C probe 1.5 m leads)

**KC1-TL3-C** (KC1 Kelvin clip 3 m leads)

**SELECT A LANGUAGE AND PLUG**

Please note only some plug types are available for certain languages - the language you need will determine the mains leads available

| LANGUAGE     |                   | PLUG TYPES AVAILABLE                                                                      |                                                                                           |                                                                                           |                                                                                            |                                                                                              |                                                                                             |                                                                                             |                                                                                                  |
|--------------|-------------------|-------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
| 3 DIGIT CODE | LANGUAGE INCLUDED | <br>UK | <br>EU | <br>US | <br>CH | <br>AUS | <br>IT | <br>IN | <br>UK + US |
| <b>LG1</b>   | EN, DE, FR, NL    | <b>P1</b>                                                                                 | <b>P2</b>                                                                                 | -                                                                                         | <b>P4</b>                                                                                  | <b>P5</b>                                                                                    | -                                                                                           | -                                                                                           | -                                                                                                |
| <b>LG2</b>   | EN, ES, PT, IT    | <b>P1</b>                                                                                 | <b>P2</b>                                                                                 | <b>P3</b>                                                                                 | -                                                                                          | -                                                                                            | <b>P6</b>                                                                                   | -                                                                                           | -                                                                                                |
| <b>LG3</b>   | EN, AR, TR, FR    | <b>P1</b>                                                                                 | <b>P2</b>                                                                                 | <b>P3</b>                                                                                 | -                                                                                          | -                                                                                            | -                                                                                           | <b>P7</b>                                                                                   | -                                                                                                |
| <b>LG4</b>   | EN, CZ, SK, PL    | <b>P1</b>                                                                                 | <b>P2</b>                                                                                 | -                                                                                         | -                                                                                          | -                                                                                            | -                                                                                           | -                                                                                           | -                                                                                                |
| <b>LG5</b>   | EN, CN, JA, KO    | <b>P1</b>                                                                                 | <b>P2</b>                                                                                 | <b>P3</b>                                                                                 | -                                                                                          | -                                                                                            | -                                                                                           | -                                                                                           | <b>P8</b>                                                                                        |
| <b>LG6</b>   | EN, RU, HU, RO    | -                                                                                         | <b>P2</b>                                                                                 | -                                                                                         | -                                                                                          | -                                                                                            | -                                                                                           | -                                                                                           | -                                                                                                |
| <b>LG7</b>   | EN, NO, SV, FI    | -                                                                                         | <b>P2</b>                                                                                 | -                                                                                         | -                                                                                          | -                                                                                            | -                                                                                           | -                                                                                           | -                                                                                                |

## ORDERING INFORMATION

| Item (Qty)                                                                                                                           | Order No.   | Item (Qty)                                                                                                                                                            | Order No. |
|--------------------------------------------------------------------------------------------------------------------------------------|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| DLRO10HDX                                                                                                                            | Configured* | Straight Duplex Handspikes (2) Heavy Duty with fixed contacts 9m/30ft                                                                                                 | 242002-30 |
| * See ordering configuration on previous page                                                                                        |             |                                                                                                                                                                       |           |
| <b>Standard included accessories</b>                                                                                                 |             |                                                                                                                                                                       |           |
| Test lead pouch (lid mounted)                                                                                                        | 1005-623    | Duplex Heavy Duty 5cm (2") C-Clamps. (2) 2m/7ft                                                                                                                       | 242004-7  |
| DLRO10HDX user guide CD                                                                                                              |             | Duplex Heavy Duty 5cm (2") C-Clamps. (2) 5.5m/18ft                                                                                                                    | 242004-18 |
|                                                                                                                                      |             | Duplex Heavy Duty 5cm (2") C-Clamps. (2) 9m/30ft                                                                                                                      | 242004-30 |
| <b>Optional Accessories at extra cost</b>                                                                                            |             |                                                                                                                                                                       |           |
| Calibration Shunt, 10 $\Omega$ , current rating 1 mA.                                                                                | 249000      | Duplex handspikes with replaceable Needle Points 2m/7ft                                                                                                               | 242003-7  |
| Calibration Shunt, 1 $\Omega$ , current rating 10 mA.                                                                                | 249001      |                                                                                                                                                                       |           |
| Calibration Shunt, 100 m $\Omega$ current rating 1A.                                                                                 | 249002      | Duplex 1.27 cm (1/2 ") Kelvin Clips. (2) gold plated 2m/7ft                                                                                                           | 241005-7  |
| Calibration Shunt, 10 m $\Omega$ current rating 10 A.                                                                                | 249003      | Duplex 1.27 cm (1/2 ") Kelvin Clips. (2) silver plated 2m/7ft                                                                                                         | 242005-7  |
| Certificate of Calibration for Shunts, NIST                                                                                          | CERT-NIST   |                                                                                                                                                                       |           |
| Replacement tips for DH4 and DH5 handspikes. Needle point                                                                            | 25940-012   | Duplex 3.8 cm (1 1/2 ") Kelvin Clips. (2) 2m/7ft                                                                                                                      | 242006-7  |
| Replacement tips for DH4 and DH5 handspikes. Serrated end                                                                            | 25940-014   | Duplex 3.8 cm (1 1/2 ") Kelvin Clips. (2) 5.5m/18ft                                                                                                                   | 242006-18 |
| Transport case                                                                                                                       | 1009-744    | Duplex 3.8 cm (1 1/2 ") Kelvin Clips. (2) 9m/30ft                                                                                                                     | 242006-30 |
| <b>Optional Test Leads at extra cost</b>                                                                                             |             |                                                                                                                                                                       |           |
| <b>Normal test leads not fitted with in-line connector:</b>                                                                          |             |                                                                                                                                                                       |           |
| Duplex Leads                                                                                                                         |             | Single handspike (1) for potential measurement. 2m/7ft                                                                                                                | 242021-7  |
| DH5 straight duplex handspikes (2).                                                                                                  |             | Single handspike (1) for potential measurement. 5.5m/18ft                                                                                                             | 242021-18 |
| One has indicator lights. 2.5m/8ft                                                                                                   | 6111-517    | Single handspike (1) for potential measurement. 9m/30ft                                                                                                               | 242021-30 |
| Terminal cover (use in conjunction with DH4 test leads supplied as standard, or optional DH5 test leads for CATIII 300 V compliance) | 1002-390    | Current clip (1) for current connections. 2m/7ft                                                                                                                      | 242041-7  |
| Duplex Handspikes (2) with spring loaded helical contacts. 2m/7ft                                                                    | 242011-7    | Current clip (1) for current connections 5.5m/18ft                                                                                                                    | 242041-18 |
| DH1 2.5m/8ft                                                                                                                         | 1006-442    | Current clip (1) for current connections 9m/30ft                                                                                                                      | 242041-30 |
| DH1 5.5m/18ft                                                                                                                        | 242011-18   |                                                                                                                                                                       |           |
| DH2 6m/20ft (only 1 lead supplied)                                                                                                   | 1006-443    | Note: For more details of optional leadsets see separate test lead datasheet DLRO_TL_DS_en_V01.pdf                                                                    |           |
| DH2 9m/30ft (only 1 lead supplied)                                                                                                   | 242011-30   |                                                                                                                                                                       |           |
| 6m ext                                                                                                                               | 1006-460    |                                                                                                                                                                       |           |
| Straight Duplex Handspikes (2) Heavy Duty with fixed contacts. 2m/7ft                                                                | 242002-7    | <b>Test leads fitted with inline connector:</b>                                                                                                                       |           |
| Straight Duplex Handspikes (2) Heavy Duty with fixed contacts 5.5m/18ft                                                              | 242002-18   | Add the part numbers of the complete lead sets and refer customers to the test lead data sheet for the individual parts                                               |           |
|                                                                                                                                      |             | For detailed information on connecting lead accessories refer to the supplied "accessory important information sheet" (DLROTestLeads--2007-431_UG_EN-DE-FR-ES-IT_V##) |           |

## SALES OFFICE

Megger Limited  
Archcliffe Road Dover  
CT17 9EN England  
T +44 (0) 1304 502101  
E UKSales@megger.com

## DLRO10HDX\_DS\_en\_V05

www.megger.com  
ISO 9001  
The word 'Megger' is a registered trademark

**Megger**<sup>®</sup>